

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County } ss.

Received for record the
16th day of DECEMBER
A. D. 1993 at 2:30 o'clock
P. M., and recorded in
Liber 4 of CORNERS
on page 310
Betty Saari, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey Section 35 T 47N R 42W

I-J-11

T R

T R

T R

2. Property Controlling S T R
in Section S T R

Other #2

3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat

5. Private Claims

Meander corner to S-26 & S-35.

November 29 93

I, John R. Garske, in a field survey on November 29, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Survey by Algernon Meriweather, June 27, 1851 - 4" balsam corner tree, 10" hemlock, S20°E, 12 links. (No original evidence found.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 4" square concrete post 14" above ground with one-half inch iron rod. Accepted corner position because of longevity and its use in many surveys in the Lake Gogebic area. This corner is apparently part of an unrecorded plat along the East Shore of Lake Gogebic as several other monuments of this type were found in the area.

I am accepting this concrete monument as being on the most probable location of the true meander corner. The monument found is substantial. I attempted to chisel the concrete in order to place a County Cap on it, however, it began breaking and I was unable to cap the monument.

PEER GROUP APPROVED

Richard H. Dralun 4/7/94
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

Established the following bearing trees and/or reference objects:

Found 4" square concrete monument with 1/2" iron rod flush with top.
24" hemlock - N27°E - 22.54 feet
5" cedar - S67°E - 10.19 feet
5" cedar - due south - 43.59 feet
6" cedar - S50°W - 10.38 feet

Concrete monument is 3 feet away from the top of bank and 6 feet from the edge of Lake Gogebic.

Signed by John R. Garske
Surveyor's Michigan License No. 28410

Date 12/27/93

