

SEP 08 1998

SECTION:

For corners in

Gogebic
(County)

Located In:

Corner Code ~~##~~

- | | | | | | |
|---------------------------------------|---|------------|---|------------|------------|
| 1. Public Land Survey | T | <u>47N</u> | R | <u>44W</u> | <u>K-5</u> |
| | T | _____ | R | _____ | _____ |
| | T | _____ | R | _____ | _____ |
| | T | _____ | R | _____ | _____ |
| 2. Property Controlling
in Section | S | _____ | T | _____ | _____ |
| | S | _____ | T | _____ | _____ |
| 3. Miscellaneous
Property in Sec. | S | _____ | T | _____ | _____ |
| | S | _____ | T | _____ | _____ |

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Section Corner 11, 12, 13 & 14: T.47 N., R.44 W.

I, Richard L. Drahn in a field survey on April 23, 19 98, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by William Burt in 1848. Original B.T.s --- Sugar 16" N.50 W. 30 links (19.80') --- Sugar 20" S.50 E. 30 links (19.80') ---

Corner position re-established by John R. Garske (28410) on 9/22/92 by double proportionate methods. He set a 2½" X 30" aluminum pipe with a 3" stamped aluminum cap and the following new bearing trees:

6"	Sugar Maple	N.35 W.	9.36'
6"	Sugar Maple	N.72 E.	16.01'
4"	Sugar Maple	S.21 W.	14.25'
6'	Steel sign rail	S.77 E.	2.43'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner recorded in Gogebic County Liber 4, Page 180 on 11/9/92.

Corner research on file with Gogebic County records.

Recovered the monument as described and the bearing trees as follows:

6"	Sugar Maple	N.33 W.	9.36'
8"	Sugar Maple	N.71 E.	16.02'
4"	Sugar Maple	S.20 W.	14.24'
6'	Steel sign rail	S.77 E.	2.42'

No evidence of the original bearing trees remain.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

7"	Sugar Maple	N.20 E.	3.79'
----	-------------	---------	-------

PEER GROUP APPROVED
Richard L. Wraim 5/13/98
COSTA REPRESENTATIVE



Signed by Richard L. Deahn Date May 4, 1998

Surveyor's Michigan License No. 21564

USFS J-21

374

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYDORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983