

OCT 8 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Gogebic
(County)

Located in:

Corner Code #

1. Public Land Survey

T 47N R 46W M 8
T 47N R 45N A-8

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Section

S T R

4. Lot No. , Recorded Plat

5. Private Claims

One-quarter section corner common to Sections 24 & 19, T47N, R45-46W.

I, John R. Garske, in a field survey on July 24, 1996,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found
as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- On September 7, 1847, John burt, U.S. Deputy Surveyor, set a sugar post with the following bearing trees:

18" Sugar - S38°E - 29 links
18" Lynn - N31°W - 30 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I established the 1/4 corner at the centerline of Ramsay Road and Plymouth Road. This position also falls in the centerline of an old
trail running north and an ancient fence line running west. The measurement of 2621.40' north to the northeast corner of Section 24
and distance checks to "40" fence lines were used to verify this position.

Record research on file.

PEER GROUP APPROVED
Richard K. Nolan 8/14/96
COUNTY REPRESENTATIVE



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

The corner position is marked by a 2 1/2" diameter x 30" aluminum pipe with 3 1/4" aluminum cap set 5" below gravel surface.
The cap is stamped: County Remonumentation, T47N, R46W-R45W, S-24, S-19, 1996, 1/4, RLS 28410. The following bearing
trees and reference objects were established:

6' Steel sign rail - N60°W - 15.93 feet
Power Pole - N22°E - 108.63 feet
Red pine - S35°E - 62.27 feet

Light pole - S30°W - 31.86 feet, also set a 3/4" x 30" iron rod with a 3 1/4" diameter aluminum cap as a reference
monument stamped: T47N, R46-45W, S-24, S-19, 1996, 1/4 cor. S60°E - 15.00, RLS 28410.

Signed by John R. Garske

Date 8-5-96

Surveyor's Michigan License No. 28410

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983