

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey

T 47N R 47W

E.F-7

008

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Meander corner common to Sections 16 and 21, T47N, R47W

I, John R. Garske, in a field survey on April 19, 19 95,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

- On August 30, 1848, William Ives used a 12" cherry as a corner tree from which a 12" fir bears S82°E, 5 links.
- 1969 Michigan Department of Transportation Highway plan shows corner position and witnesses.
- 1977 corner search by John R. Garske, R.L.S. No evidence found.
- 1993 - Subsequent field search by John R. Garske, R.L.S. No evidence found.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I reestablished the corner position by extending the section line common to Sections 16 and 21 until intersecting the bank of the
Montreal River. I was able to set a point on line 362.14 feet east of said meander corner and actually run true line to river and by
doing so were able to find an ancient fence line on our true line. I have determined that this is the best and most probable location for
the corner position.

Record research on file with Register of Deeds.

BEER GROUP APPROVED

Richard P. Dean 7/18/95

COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I set 2-4 foot sections of 3/4" diameter aluminum marsh rod with a 3 1/4" diameter aluminum cap stamped: County
Remonumentation; T47N, R47W; M.C.; S-16; S-21; 1995; RLS 28410, from which I established the following bearing trees
and/or reference objects:

- 20" silver maple - N35°E - 31.62 feet
- 18" silver maple - S79°E - 20.71 feet
- 16" silver maple - S39°W - 12.94 feet
- 6' steel rail with sign - due west - 1.00 feet
- Edge of river - due west - 8.5 feet
- Edge of slough - due east - 74.8 feet

Signed by

John R. Garske

Date

5/4/95

Surveyor's Michigan License No. 28410

