

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.  
Gogebic County }

For corners in

Gogebic  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 47N R 47W

H-I-13

T 46N R 47W

H-I-1

2. Property Controlling  
in Section

S

T

R

3. Miscellaneous  
Property in Sec.

S

T

R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Meander corner common to Section 34, T47N, R47W and Section 3, T46N, R47W

I, John R. Garske, in a field survey on April 20, 19 95,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- On 1847, William A. Burt set a Y. birch post from which a 10" fir bears S60°E, 80 links and an 8" fir - N67°E, 77 links.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of this corner could be found. I reestablished the corner position by extending the section line common to Sections 34  
and 3 until intersecting the bank of the Montreal River. I believe that this is the only possible location for this corner as no other  
information exists.

Record research on file with Register of Deeds.

PEER GROUP APPROVED  
Richard P. Decker 7/18/95  
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I set a 2 1/2" diameter x 30" long aluminum pipe with a 3 1/4" diameter aluminum cap stamped: County Remonumentation;  
T47N, R47W, T46N; M.C.; S-34; S-3; 1995; R.L.S. 28410, from which I established the following bearing trees and/or reference  
object:

- 7" spruce - N83°E - 15.78 feet
- 10" spruce - S43°W - 5.83 feet
- 10" spruce - N24°W - 4.53 feet
- 6" steel rail with sign - S35°E - 1.37 feet
- Edge of river - Due West - 6.5 feet
- Corner is set in 60# of concrete

Signed by John R. Garske Date 5-4-95  
Surveyor's Michigan License No. 28410

