

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County }

For corners in

GOGEBIC

(County)

Located In:

Corner Code #

1. Public Land Survey

T48N R 44W F-11

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

SURVEY &
REMONUMENTATION

JAN 05 2001

SECTION

4. Lot No. , Recorded Plat

5. Private Claims

Quarter corner, Sections 28 & 33, T48N, R44W

I, John P. Goss, in a field survey on Sept. 20, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	13		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt, in 1848.

Original bearing trees: Yellow Birch 12" S 54° E 19 links (12.54 ft.)
Sugar Maple 16" N 57° W 14 links (9.24 ft.)

Donald D. Lappala, 12585, on Sept. 28, 1972, restored corner position at record bearing and distance from the decayed remains of the two original bearing trees. He set a 2" I.D. iron pipe with 3" brass tablet stamped, to indicated the corner position. He established the following reference objects:

12" S. Maple N 68° W 13.6 ft.; 8" S. Maple N 58° E 22.8 ft.;
10" S. Maple S 13° E 19.1 ft. Metal sign post N 28° E 1.5 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

He recorded said corner in U.S.F.S. Liber, Index No. V-11, on Dec. 9, 1974.

Found Donald D. Lappala monument and accessories.

Act 74 research on file.

PEER GROUP APPROVED

Richard L. Drahm 9/21/00
COUNTY SURVEILLATOR

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From found monument stamped to read: T.48 N., R.44 W.; 1/4; S-28, S-33; R.L.S. 12585; 1972; from which I established the following existing and new reference objects:

15" Sugar Maple N 68° W 13.76 ft.
11" Sugar Maple N 58° E 22.85 ft.
14" Sugar Maple S 13° E 19.29 ft.
7" Sugar Maple S 28° W 40.32 ft.
Metal sign post N 38° E 1.58 ft. to face
(All measurement taken to nail in side of tree)



Signed by John P. Goss

Date Sept. 20, 2000

Surveyor's Michigan License No. 23509

U.S.F.S. No. V-11