

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office
Gogebic County ss.

For corners in

GOGEBIC
(County)

Located in:

Corner Code #

1. Public Land Survey

T48NR 44W G-12

T R

T R

T R

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

3. Miscellaneous
Property in Sec.

S

T R

JAN 05 2001

Quarter corner, Sections 33 & 34, SECTION 4W

4. Lot No. , Recorded Plat

5. Private Claims

Received for record the
26th day of OCTOBER
A. D. 1900 at 1:20 o'clock
P. m., and recorded in
Liber 8 of CORNERS

on page 42

Yammy L. Stella, Dep
Register of Deeds

Register of Deeds Stamp & File Number

I, John P. Goss, in a field survey on Sept. 27, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Austin Burt, in 1848.

Original bearing trees: Fir 6" S 66°E 8 links (5.28 ft.)
White Pine 12" N 78°W 25 links (16.50 ft.)

Donald D. Lappala, 12585, on Sept. 12, 1972, restored corner position at record bearing and distance from the the white pine bearing tree. Corner position verified further by retracement measurement of the section line north and south from corner to recoverable natural features and line trees. He set a 2" I.D. iron pipe with 3" Brass tablet stamped, to indicated the corner position. He established the following reference objects.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

6" Tamarack - N 84° W - 38.9 ft.; 8" Tamarack - S 56°W - 32.5 ft.
5" Tamarack - S 69° W - 39.0 ft.; Metal sign post - N 08°E - 2.5 ft.
He recorded said corner on Dec. 9, 1974, in U.S.F.S. Liber, Index X-13.

Found Donald D. Lappala Corner and accessories.

Act 74 research on file with county.

DEER GROUP AFFILIATION
Richard L. Dean 10/25/00
COUNTY DEER

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From found monument stamped to read: T.48 N., R.44 W.; 1/4; S-33, S-34; 1972; R.L.S. 12585, from which I established the following existing and new reference objects:

8" Tamarack N 84° W 39.07 ft.
9" Tamarack S 56° W 32.38 ft.
7" Tamarack S 69° W 39.09 ft.
6" Maple N 60° W 16.90 ft.
Metal sign post N 08° E 2.5 ft. to face
(All measurement taken to nail in side of tree)



Signed by John P. Goss
Surveyor's Michigan License No. 23509

Date September 28, 2000

U.S.F.S. #X-13