

SURVEY &
REMONUMENTATION

OCT 03 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 48N R 44W.

H-11

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

$\frac{1}{4}$ Corner 27 & 34; T.48 N., R.44 W.

I, Richard L. Drahn in a field survey on June 1, 19 96,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on Sept. 7, 1848. Original B.T.s ---
Y. Birch 18" S.80 W. 26 links (17.16') --- Sugar 18" N.76 E. 23 links
(15.18'). Corner restored by Donald D. Lappala, RLS 12585 from the
remains of the two original B.T.s, a line tree east and a natural feature
tie west. He set a 2" dia. iron pipe with a 3" stamped brass cap and the
following new bearing trees on 9/15/72: --- 8" (10") Sugar Maple N.36 W.
(N.38 W.) 28.6' (28.55') --- 9" (13") Sugar Maple N.53 E. (N.54 E.) 30.8'
(31.02') --- 5" Red Maple (now dead and down) S.37 W. 29.7' --- Metal
sign post N.01 W. (N.01 W.) 1.9' (2.0')---

Corner recorded in Gogebic County in USFS Liber, Page V-15 on 12/9/74.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Act 74 research form on file with Gogebic County records.

Recovered the monument as described and the bearing objects as noted in
parentheses above. A Y. Birch stump and a stump hole still remain from
the original bearing trees.

PEER GROUP APPROVED

Richard L. Drahn 6/6/96
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

9" Sugar Maple S.05 E. 5.99'



Signed by Richard L. Drahn

Date June 2, 1996

Surveyor's Michigan License No. 21564