

MAY 13 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office  
Gogebic County

Recorded for record the  
17<sup>TH</sup> day of OCTOBER  
A. D. 1996 at 9:50 o'clock  
A. M., and recorded in  
Liber 6 of CORNERS  
on page 78  
Ramona Collins, Deputy  
Register of Deeds

Register of Deeds Stamp & File Number

For corners in

Gogebic  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 48N R 44W

L-7

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

1/4 Corner 13 & 24; T.48 N., R.44 W.

I, Richard L. Drahn in a field survey on October 1, 19 96  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on Aug. 29, 1848. Original B.T.s ---  
Fir 10" S.65 E. 21 links (13.86') --- Fir 12" N.70 W. 35 links (23.10') ---

Corner re-established by Richard L. Drahn, RLS 21564 on 7/31/89 equal distance  
from recovered corners 1/2 mile east and west and on line with old fence lines  
east and west.

He set a 2" X 1 1/2' iron pipe with a 3" stamped brass cap sub-surface and the  
following new bearing objects: --- 6" (7") Red Maple S.67 W. (S.68 W.) 14.45'  
(14.35') --- 4" (5") Sugar Maple N.78 W. (N.76 W.) 26.76' (26.82') ---

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

6" Aspen N.54 E. (N.54 E.) 54.83' ( 54.93') --- 6' Steel rail West (West)  
18.7' (18.58') --- 2" X 4' iron pipe Reference Monument with a 3" stamped  
brass cap West (West) 16.50' (16.41') ---

Recovered the monument as described and the bearing trees as noted in  
parentheses above. No evidence remains of the two original B.T.s

Corner recorded in Gogebic County in Liber 3, Page 314 on 1/23/90.

Act 74 research form on file with Gogebic County records.

PEER GROUP APPROVED

Richard L. Drahn 10/16/96  
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

No new bearing objects referenced.



Signed by Richard L. Drahn

Date October 2, 1996

Surveyor's Michigan License No. 21564