

SEP 08 1998

SECTION
For corners in

Gogebic
(County)

Located in:

Corner Code #

- | | | |
|-------------------------|-------------|------|
| 1. Public Land Survey | T 48N R 45W | E-11 |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling | S T R | |
| in Section | S T R | |
| 3. Miscellaneous | S T R | |
| Property in Sec. | S T R | |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Section Corner 28, 29, 32 & 33; T.48 N., R.45 W.

Richard L. Drahn, in a field survey on July 7, 1998, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on 9/25/1848. Original B.T.s --- Hemlock 20" S.10 W. 32 links (21.12') --- Hemlock 24" N.19 E. 50 links (33.00') --- Supercynski on 5/10/35 recovered the NE B.T. still scribed. Corner restored by Richard L. Drahn (21564) on 6/7/84 from the remains of the two original B.T.s and Supercynski's tag tree. He set a 2" X 30" alum. pipe with a 3/4" stamped aluminum cap and the following new B.T.s:

15" Hemlock	N.53 W.	41.42'
9" Cedar	N.30 E.	25.96'
Chiseled "X" in rock	S.38 W.	14.81'
6' Steel rail	N.54 E.	4.35'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner recorded in Gogebic County Liber 2, Page 677 on 12/10/84.

Corner research on file with Gogebic County records.

Recovered the monument as described and the bearing trees as follows:

17" Hemlock	N.53 W.	41.50'
11" Cedar	N.30 E.	26.50' (new nail)
"X" in rock	S.48 W.	14.80'
6' Steel sign rail	N.55 E.	4.34'

Decayed Hemlock stumps still remain from the original B.T.s.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree established:

10" Red Maple	S.68 E.	44.78'
---------------	---------	--------

Resource grade GPS	Lat	46-31-13.52'N
	Long	89-56-55.25 W

PEER GROUP APPROVED

Richard L. Drahn 7/22/98
COUNTY REPRESENTATIVE



Register's Office
Gogebic County

Received for record the
23rd day of JULY

A. D. 1998 at 11:40 o'clock

A. M., and recorded in

Liber 7 of CORNERS

on page 37.

Ramona Collins Deputy
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Signed by Richard L. Drahn Date July 19, 1998

Surveyor's Michigan License No. 21564