LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Grand Traverse (County)	Located In	Corner Code #	
1. Public Land Survey	T R T R		
Property Controlling in Section	S 34 T 25N R 11W S 34 T 25N R 11W		
Miscellaneous Property in Section	S T R R		Register of Deeds Stamp & File Number
4. Lot No: 5. Private Claims:	Recorded Plat:		A B C D E F G H I J K L M
_	field survey on April 11, 2012 do h	pereby state that under	3
requirements of PA 74, Mi and 2 above were in confo the current manual of sur	ichigan PA of 1970, the corner poin ormance with regulations and rules to rvey instructions of the United State anagement or by a decree of a Cour	ts mentioned in lines 1 therefore as required in tes Department of the	4 7 8 9 10 11 12 12 15 16 15 14 13 15 16 15 16 16 16 16 16 16 16 16 16 16 16 16 16
of the Michigan Board of	lines 3, 4 and 5 above were in conf of Land Surveyors or by a Decre I, monumented, recovered, found as	e of a Court of Law;	7 8 —19 —20 —21 —22 —23 —24 9
NOTE: Not more than 2 corners, all in the same town and range, may			10302928272625

- A. Description of original monument and accessories and/or subsequent restoration:
- 11 2004 LCRC 2004L 00012; C. W. McVean. Set Stamped 2" Alum. Cap on 5/8" x 34" rebar.

 1) Fd. a pipe N84°55'E 5.2'; 2) N8°W 84.20' to set N & T in E. side 7" Basswood; 3) N56°E 20.66' to set N & T in N. side Tw. 5" Cherry; 4) S22°E 34.32' to set N & T in E. side 8" Elm; 5) N89°W 61.05' to set N & T in S. side Tri. 6" Cherry. Set Blue Carsonite Post 1' NE.

be recorded on this certificate.

- 12 2004 LCRC -- 2004L -- 00012; C. W. McVean. Set Stamped 2" Alum. Cap on 5/8" x 34" rebar. Corner of fence S & W is 3'W and 10.5'N. 1) N72°W 84.51' to set N & T in S. side 9" Maple; 2) N58°W 36.20' to set N & T in S. side 11" Maple; 3) N2°E 117.15' to set N & T in E. side 12" Maple; 4) S36°E 176.17' to set N & T in S. side 8" Fir; Set Blue Carsonite Post with loc. tag 1' NE.
- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- 11 SW 1/16 Cor. Sec. 34 Set 2" Alum. Cap on 5/8" x 34" iron rebar per Standard BLM procedure. Line of wood post to N. is 4' West. Line of wood post to E. is 1' South.
 - Reference Pt. 'U' Found 2" Alum. Cap on 5/8" x 34" rebar set in 2004 is N89°49'W 3.37' from cor. '11'. This position is based on rejected positions at corners 'H11', G13', and 'I-12'. Removed this 2" Alum. Cap monument.
- 12 CS 1/16 Cor. Sec. 34 Set 2" Alum. Cap on 5/8" x 34" iron rebar per Standard BLM procedure. Line of wood post to the West is 1'± North.
 - Reference Pt. 'V' Fd. 2" Alum. Cap on 5/8" x 34" rebar set in 2004 is N72°29'W 7.85' from cor. '12'. This position based on rejected positions at corners 'H11' and 'I-12'. Removed this 2" Alum. Cap monument.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- 11 Stamped 2" Alum. Cap on 5/8" x 34" long iron rebar Reset Blue Carsonite Post with loc. tag 1' NE S84°W 64.34' to fd. N & T in S. side Tri. 6", 8" and 10" Cherry (#5) N14°W 84.75' to fd. N & T in E. side 10" Elm (#2) N51°E 18.02' to fd. N & T in NW side 6" Cherry (#3) S6°W 61.89' to set N & T in E. side Tw. 10" and 12" R. Maple
- 12 Stamped 2" Alum. Cap on 5/8" x 34" long iron rebar Reset Blue Carsonite Post with loc. tag 1' NE N2°W 119.65' to fd. N & T in E. side 15" S. Maple (#3) S34°E 169.95' to fd. N & T in SW side 11" B. Fir (#4) N72°W 92.33' to fd. N & T in S. side 7" S. Maple (#1) N56°W 43.77' to fd. N & T in S. side 13" S. Maple (#2)

Signed by:	Cruy	W.	Millen	
Surveyor's M	ichigan License I	No.:	39088	

Date: 11/14/2012

CRAIG W.
MCVEAN
PROFESSIONAL

NO.
39088

**OFESSIONAL

MAY 14

MAY 14