

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

**GRAND TRAVERSE**

(County)

Located In:

Corner Code #

1. Public Land Survey

T 26N R 11W

1-11

T R

T R

T R

2. Property Controlling in Section

S 27

T R

13,14,16

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, CARL F. ROSE, in a field survey on OCTOBER 8, 19 84, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1-11

13

14

16

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1-11

13

14

16

SE COR 8-27, FB ROUND CONC MON AS SET BY L.S., J. WILCOX PER E.P. WATERMAN 1910 ROAD SURVEY IN 8-34, T26N, R11W.

ESTAB'D CTR OF SE 1/4 OF 8-27 PER STANDARD BLN INSTRUCTIONS. CTR OF GRAVEL RD IN CURVE, (RD W & S) IS 645°N, 36'±.

ESTAB'D SE COR OF NE 1/4 - SE 1/4 OF 8-27 PER STANDARD BLN INSTRUCTIONS. COR IS IN APPROX CTR OLD N-S RD GRADE.

FB 1" PIPE FOR E 1/8 COR ON S LINE 8-27. SEE E.P. WATERMAN FIELD BOOK, VOL 24, PG. 11 (1914). COR IS IN APPROX LINE W/FN S. AN E-W FN IS 12' S. CTR PVT RD S IS 6'±N. CTR OF WINDING E-W ROAD TO E IS N 8'±.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1-11

13

14

16

FB ROUND CONC MON & SET CED POST W/LOC TAG.

DROVE 5/8" X 34" REROD W/RLS CAP & SET CED POST W/LOC TAG.

DROVE 5/8" X 34" REROD W/RLS CAP.

FB 1" PIPE (BURIED 0.3')

16" BEECH N26°E 14.76'  
5" MAPLE N82°E 8.32'  
8" MAPLE S22°W 13.79'  
5" ASH N62°W 10.32'

10" CEDAR N48°E 34.5'  
17" CEDAR N46°W 19.0'  
DR 5/8" X 34" REROD W/  
RLS CAP N00°10'22"W 33.86'  
DR 5/8" X 34" REROD W/  
RLS CAP S89°56'10"E 31.86'  
DR 3/8" X 24" PIPE  
FOR RD PT N21°54'18"W 3.08'

10" MAPLE N42°W 24.5'  
14" MAPLE N08°E 36.4'  
12" ASH S62°E 19.5'  
SET CED POST W/  
LOC TAG. WEST 16.5'

\*12" MAPLE S75°W 36.63'  
12" MAPLE THIN S70°E 25.30'  
8" CHERRY N10°W 39.20'

\* = OLD WIT.

Signed by Carl F. Rose 10-25-88 Date

Surveyor's Michigan License No. 12028

