

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
**GRAND TRAVERSE**  
(County)

Located In:

Corner Code ##

1. Public Land Survey T 24N R 11W 6-9  
T        R        H-9  
T        R        I-9  
T        R         
2. Property Controlling S 22 T        R        15  
in Section S        T        R         
3. Miscellaneous S        T        R         
Property in Sec. S        T        R       

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, CARL F. ROSER, in a field survey on OCTOBER 15, 19 84,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law, established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

6-9

H-9

I-9

15

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

6-9

H-9

I-9

15

FD 1/2" ROD W/J. WILCOX'S RLS  
CAP INSIDE 2" PIPE, FOR NW COR  
S-27. DROVE 1" X 60" PIPE  
INSIDE 2" PIPE IN PLACE OF  
1/2" ROD & RIVETED DNR ALUM  
CAP ON 1" PIPE.

FD 1/2" ROD W/J. WILCOX RLS CAP  
INSIDE OF 2" PIPE FOR N 1/4  
COR S-27. DROVE 1" X 66" PIPE  
W/DNR ALUM CAP INSIDE OF 2"  
PIPE IN PLACE OF 1/2" ROD. FD  
OLD 60 POST 80'±S & 25'±E.  
COR IS IN CED SWAMP.

FD AXLE SHAFT FOR NE COR S-27. ESTAB'D SE COR OF SW 1/4 OF SW  
A POSITION PER TWO POSSIBLE 1/4 OF S-22 PER STANDARD BLM  
E.P. WATERMAN WIT. (PINE STP 30 INSTR. COR FALLS IN APPROX  
S72°E 55.6' & PINE STP 48 640' CTR OF GAS LINE OPENING THAT  
W 79.6') FROM 1917 SURVEY RUNS NE-SW.  
WOULD BE 0.7' S & 4.4' W OF  
AXLE SHAFT.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

6-9

H-9

I-9

15

FD 1/2" X 18" ROD W/RLS CAP  
#14102 INSIDE 2" X 14" PIPE;  
REPL'D W/1" X 60" PIPE W/DNR  
CAP & SET CED POST.  
16" W. PINE N28°W 24.76  
+ 6" CEDAR N22°E 24.66  
+ 9" CEDAR S34°E 16.14  
+ 6" CEDAR S72°W 20.50

FD 1/2" X 18" ROD W/CAP #14102  
INSIDE 2" X 12" PIPE; REPL'D  
W/1" X 66" PIPE W/DNR CAP &  
SET CED POST.  
12" CEDAR S52°E 26.00  
+ 14" CEDAR S36°W 7.90  
+ 10" CEDAR S12°W 15.00  
+ 16" CEDAR N30°W 11.87  
12" W PINE N30°E 18.1

FD LARGE AXLE SHAFT IN SAND  
TRAIL INTERSECTION.  
+ 8" W PINE N48°E 49.53  
+ 28" W PINE S40°E 104.00  
+ 7" W BIRCH N44°W 60.11  
SET CED POST W/  
LOC TAG. S45°W 47.5'

DROVE 3/8" X 60" PIPE W/RLS  
CAP & SET CED POST W/LOC TAG.  
8" CED S70°E 29.2  
6" CEDAR N08°E 38.3  
11" CEDAR N55°W 28.2

+J. WILCOX WITS

+FD WITS PER J. WILCOX NOTES.

+D. BONGIOVANNI WITS

Signed by Carl F. Roser 10-25-88 Date

Surveyor's Michigan License No. 12028

FORM APPROVED BY MICHIGAN STATE BOARD OF

