				ERTIFICATE	BITATE BUT VERLEY
For Corners In:	гинд	Requirement of	Act 74, Mich.	PA 1970 	STATE OF HICHIGAN GRAND TRAVERSE COUNTY
Grand Traverse (County)	Located In	Corner C	Code#		RECORDED 30 DEC 99 4:06 P.M.
1. Public Land Survey	T 27N R	9W <u>M-6</u>			KARON ANDERSON
Property Controlling in Section	s				REGISTER OF DEEDS
3. Miscellaneous		SURVEY EMONUME	Y & . NTA TION		
Properly in Section	S T R S T R	MAR 222			
4. Lot No:	Recorded Plat:		<u>.uuu</u>	Register of	Deeds Stamp & File Number
5. Private Claims:		SECTIO	N	A B C D E	FGHIJKLM
requirements of PA 74, Mic and 2 above were in confor the current manual of surv Interior, Bureau of Land Mar corner points mentioned in I of the Michigan Board of established, re-established,	eld survey on Nov. 1, 1999 higan PA of 1970, the corner mance with regulations and rey instructions of the Uniter nagement or by a decree of a ines 3, 4 and 5 above were in Land Surveyors or by a Emonumented, recovered, four	r points mentioned in the points therefore as red states Department Court of Law and/or a conformance with the poerree of a Court and as expressed belonger the points of	n lines 1 quired in nt of the that the the rules of Law; ow:	2 6 5 3 4 7 8 5 6 18 17 7 7 8 19 20 9	9 — 10 — 11 — 12 — 14 — 13 — 14 — 13 — 12 — 14 — 13 — 14 — 13 — 14 — 15 — 14 — 15 — 14 — 15 — 15 — 14 — 15 — 15
NOTE: Not more than 2 be recorded on this cert	corners, all in the same lificate.	town and range,	may	10 -30 -29 -11 12 -3 -32 -13	28 27 26 25 13 35 36
A. Description of original	monument and accessorie	s and/or subseque	ent restoration:		
 M. Schaaf – 1930' - corner set by measing the corner recorner recorner recorner found 1" pipe in confine with fire line in may have been set would fall in Rd. & sevidence to contrary 	0 L., Aspen 4" 18-27-8-Survey Bk. 32, P. 1 urement per index id -K.J.Ostling – 1967 increte mon. per M. Schaal N,S,E&W from original evidence alt itp. Have been removed. U y so accepted this as best pe with 4" Alum. cap	f –1934. hough USBT Inable to find available	Found concrete LCRC L.3 , pp C.F. Roser-19 5" Maple N 16" W. Pine N 8" Maple S 9" R. Pine S	95 - found Conserv √60°W 22.0'	erse County record-
B. Description of corner ev	idence found and/or meth	od applies in resto	ring or re-estab	lishing corner:	
Centerline of N-S fin 3 ¼ " brass cap mon -Reference PtFoun position that Schaaf i S4°51'W 40.58' of the	accepted as a careful & d d DOC (DNR) 4" Alum cap ndicates he set by measured approved M-5 position. T	cap on 2 ½ " X 30 rline of E-W fire lin faithful reestablish & mon S22°16' rement. The M. Schus DOC Mon. co	" galvanized iro le is 24' South. ment of the pos W 25.80' of M-0 haaf position 1/2	on pipe by single prosition of the original 3. This DNR mon. be mile N was rejected to the property	oportion between M-5 & M-7.
	nt for corner and accessori		•		he corner:
N34°E 17.11' S87°E 36.14' S45°W 62.40' N85°W 22.75'	te Co. Remon.' Brass cap with tag N 0.85' to face to set N&T in W side to set N&T in S side to set N&T in NW side to set N&T in S side to set N&T in S side to 1 1/4" iron pipe stub in coost w/ loc. Tag 1' E	11" R. Pine scribe 12" W. Pine scribe 9" R. Pine fnd. s 15" R. Oak scribe	ed 'XBT' ed 'XBT' cribed '¼ S NB d 'XBT'		CRAIG W. MCVEAN PROFESSIONAL SURVEYOR NO. 39088
Signed by: Surveyor's Michigan Lice UNANIMOUSLY ACCEI GRAND TRAVERSE CI REVIEW GROUP AS T CORNER UNDER MICH ACT 345 OF 1990 AT	PTED BY THE OUNTY PEER HE OFFICIAL HIGAN PUBLIC	Vean	Date: /2	2/13/1999	39088 JE
HELDON 32	799	FORM APPROVE) ВУ МІСНІСАМ ОТ	ATE ROADD OF SDOC	SSIONAL SURVEYORS JAN. 28, 1971
ROBERT F. MITCHELL, F	.S., CI IÄlinMAN	The state of the s	ST MOTHORN ST	WE BOARD OF PROFE	SSIONAL SURVEYORS JAN. 28, 1971 Revised May 14, 1975 Revised Jan. 1983