

Filing Requirement of Act 74, Mich. PA 1970

Corner Code #

Register of Deeds Stamp & File Number

5. Private Claims:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

A-8 & M-8 -Standard ¼ corner common to Sec. 19, T27N R9W & Sec. 24, T27N R10W. - Set 3 ¼" 'Grand Traverse. Co. Remon.' brass cap on 2 ½" x 30" Galv. Iron Pipe per C.P. Tuller's Rec. Wits. as follows: S57°W 11.15' to set spike in CL. remains 24" + burnt White Pine Stp. (GLO) and N12°W 51' to axed face (add nail & tag) on 18" R. Pine Stp. (CPT). 3 ¼" brass cap mon. accepted as a careful & faithful perpetuation of the position of the original corner.

-Reference Pt. -FND. 1 1/2" I.D. Iron Pipe stub in conc. tablet by M. Schaaf & used by Perla - N34°58'W 33.75' of A8-M8. A Pine Stp. that appears to be a twin is at GLO bearing & dist. SW. Schaaf notes he had line trees N & S. Did find a 28" WPS (24" Pine-320'-GLO) 317'± 2' North of Schaaf Mon. but couldn't say it was conclusive. Based on the SW PS being an apparent twin and that Tuller was here 40+ years before Schaaf couldn't accept Schaaf's monument. Schaaf monument not utilized as A8-M8 in this survey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-8 & M-8 -3 1/4" 'Grand Traverse Co. Remon.' brass cap on 2 1/2" x 30" galvanized iron Pipe in ring of broken concrete.
Set Blue Carsonite Post w/ loc. Tag 1' E.
N59°W 12.09' to N & T in S side 12" R. Oak scribed 'XBT'
S44°E 12.63' to N & T in SW side 1" R. Pine
S65°W 26.67' to N & T in NW side 3" W. Pine
N16°E 59.92' to S & T in E side 8" W. Pine scribed 'XBT'
N34°57'W 33.75' to 1 1/2" Iron Pipe stub in conc.-M. Schaaf Mon.-Ref Pt.

Signed by:

Surveyor's Michigan License No.: 39088

Date: 17/13/1999

