

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Grand Traverse

(County)

Located In

Corner Code #

1. Public Land Survey

T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_

2. Property Controlling  
in Section

S 14 T 27N R 9W 4  
S 14 T 27N R 9W 6

3. Miscellaneous  
Property in Section

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Craig W. McVean, in a field survey on June 28, 2000 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

4 -None

6 -None



B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

4 - NW 1/16, Sec. 14, T27N, R9W  
Set 2" Alum. cap on 5/8" x 34" Rebar per Standard BLM  
Procedure. Corner of fence barbwire N & E is 2' E. & 13' N.

6 - NE 1/16, Sec. 14, T27N, R9W  
Set 2" Alum. Cap on 5/8" x 34" Rebar per Standard BLM  
procedure in CL of 2 track rd.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

4 - 2" AC on 5/8" x 34" Rebar  
N40°W 80.74' to N&T in SW side 11" R. Pine  
S50°W 32.24' to N&T in NW side 16" R. Pine  
S42°E 30.35' to N&T in NE side 8" J. Pine  
N14°E 13.59' to N&T in E. side 9" Wood Anchor Fence  
Post (N&E).  
Set Blue Carsonite Post w/ loc. tag 1' SW

6 - 2" AC on 5/8" x 34" Rebar  
S85°E 37.44' to N&T in N. side 14" S. Maple  
S43°E 7.20' to N&T in SW side 10" Basswood  
S71°W 38.78' to N&T in S. side 12" S. Maple  
N 38.51' to N&T in E. side 4" S. Maple  
Set Blue Carsonite Post w/ loc. tag 20' S.

Signed by:

*Craig W. McVean*

Date:

*1/22/2001*

Surveyor's Michigan License No.:

39088