

MAR 16 1994

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
GRAND TRAVERSE COUNTY
RECORDED

30 DEC 93 10:20 A.M.

KAREN ANDERSON
REGISTER OF DEEDS

For corners in **COMMISSION**
GRAND TRAVERSE
(County)

Located In: Corner Code #/

- | | | | | | |
|---------------------------------------|---|-----|---|-----|-----|
| 1. Public Land Survey | T | 27N | R | 11W | E-9 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling
In Section | S | | T | R | |
| | S | | T | R | |
| 3. Miscellaneous
Property in Sec. | S | | T | R | |
| | S | | T | R | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, **Gary G. Wilson**, in a field survey on **December 17**, 19 **93**,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

E-9:GLO information, County Surveyor Records dated 12-24-1891 (Liber 1, Page 389)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

**E-9: No physical evidence of the original GLO witnesses were found.
Found 1" iron bar in stone pile on East & West fence line.**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**E-9: Corner common to Sections 20, 21, 28 & 29
Perpetuated with 2-1/2" X 30" flanged bottom galvanized iron pipe with 3-1/2" brass cap stamped GRAND
TRAVERSE COUNTY REMONUMENTATION.**

**S56°W 72.72' Twin 12" Maple
S31°E 57.67' Triple 20" Basswood
East 4.47' 6" Elm
N59°W 34.51' 6" Elm**

Corner approved by the Grand Traverse County Peer Review Group on 11-03-93.

Signed by Gary G. Wilson, PS
Surveyor's Michigan License No. 25881

Date December 28, 1993

