

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: October 27, 2016

For corner(s) in: Houghton County

Original Public Land Survey Corner

Corner Code

a. S T 51N R 35W
 S T R
 S T R
 S T R

F5 (GCDB 340500)

Property Corner

1/16 Corner Code

b. S 20 T 51N R 35W
 S T R
 S T R
 S T R

11 (GCDB 220320)

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2	6			5		4		3		2		1		2
3														3
4	7		8			9		10		11		12		4
5						●								5
6	18		17			16		15		14		13		6
7														7
8	19		20			21		22		23		24		8
9			●											9
10	30		29			28		27		26		25		10
11														11
12	31		32			33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A. Corner History

a.) Quarter corner common to Sections 9 and 16. 1848 - Established by S.W.Higgins, Deputy, midway and on the Section line between Section corners 40.05 chains east and west. Set post. Sugar 10" N45°E 14 links, Maple 12" S73°E 16 links. Found no subsequent record.

b.) Southwest 1/16 corner, Section 20. Not previously monumented.



Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of

a.) The original post and accessories were not recovered. Found no evidence of the position of the original corner on the ground. Reestablished the position for the corner midway and on the Section line between Section corners 2629.70' east and west, proportionate to the original record. A very old open blaze found on a dead 22" Hemlock faces the position monumented.

b.) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the East and West being monumented.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

(a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 4" Sugar S64°E 12.1' mrkd "1/4S NBT"
 5" Y.Birch S24°E 24.8' do
 8" Y.Birch N76°W 5.4' do
 3" Sugar N35°W 11.05' do
 Set sq'd cedar post adjacent.
 E= 7866286.286 N= 228186.763

(b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 4" Sugar N32°E 24.05' mrkd "1/16S BT"
 4" Sugar N73°E 11.4' do
 7" Sugar S75°E 14.5' do
 22" Hemlock N73°W 20.9' do
 Set sq'd cedar post adjacent.
 E= 7864206.632 N= 225388.677

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meters.
 Coordinate Reference: NGS PID RL0593, E= 7868965.488 m. N= 221669.506 m.

Stephan J. Szyszkoski

01/04/2017

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908