

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T 51N R 35W	K2
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 04/02/2008 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(K2) Quarter corner common to Sections 1 and 2. 1969 - A.O.Enger RLS remonumented the corner
position as determined from local evidence. Set 1"IDx36" Iron pipe with 4" aluminum cap. Sugar
Maple 5 S71E 17.5 links, Sugar Maple 5 S81W 23 links. Mr. Enger's corner record was filed in 1971.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(K2) Recovered the 1969 monument in good condition and at record bearing and distance from the 1969
NBT Sugar SW, standing but nearly dead, with overgrown blazes visible. The Sugar NBT SE was not
apparent. Accepted the monument as the best available evidence of the position of the original
corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(K2) Found 1"ID I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Sugar N86E 7.4' mrkd "1/4S NBT"
7" Sugar S30E 14.2' do
6" Sugar S30W 20.0' do
4" Sugar S88W 14.4' do
Bearings are magnetic.



Signed by Stephan J. Szyszkoski Date 05/19/2008
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971