

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 23 T 51N 36W	16
	S 24 T 51N R 36W	11
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Stephan J. Szyszkoski, in a field survey on 10/08/12 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(16-Sec. 23) East 1/16 corner between Sections 23 and 26. Not previously monumented.

(11-Sec. 24) Southwest 1/16 corner, Section 24. Not previously monumented.

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(16-Sec. 23) Established the position for the corner midway and on the Section line between Section corner 1343.38' east and Quarter corner 1343.38' west.

(11-Sec. 24) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(16) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Sugar N81°E 19.8' mrkd "1/16S BT"
7" Sugar S28°W 14.0' do
6" Maple S69°W 12.7' do
5" Sugar N74°W 12.1' do
Set sq'd cedar post adjacent.

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" W.Spruce N87°E 5.7' mrkd "1/16S BT"
7" Sugar S23°W 13.1' do
4" Y.Birch S64°W 4.5' do
4" Y.Birch N18°W 13.1' do
Set sq'd cedar post adjacent.

Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 01/09/2013

For the Michigan Department of Natural Resources, Forest Resources Division

