

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

<u>Houghton</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 24 T 51N R 36W	9
	S 25 T 51N R 36W	9
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 9-Sec.25 10/10/12 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 24) East 1/16 corner, Section 24. Not previously monumented.

(9-Sec. 25) East 1/16 corner, Section 25. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 24) Established the position for the corner midway and on a straight line between Quarter corner 1331.30' east and the Center of Section 24 1331.30' west.

(9-Sec. 25) Established the position for the corner midway and on a straight line between Quarter corner 1363.14' east and the intersection of 1/4 lines of Section 25 1363.14' west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9-24) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
14" Y.Birch N63°E 22.3' mrkd "1/16S BT"
5" Sugar S72°E 18.2' do
6" Elm S42°W 19.95' do
4" Sugar N10°W 10.6' do
Set sq'd cedar post adjacent.

(9-25) Set 1"IDx32" I.pipe w/ 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
3" Maple in clump N19°E 3.5' mrkd "1/16S BT"
3" Maple S52°E 25.7' do
5" Y.Birch S42°W 43.9' do
5" W.Ash N67°W 13.3' do
Set sq'd cedar post adjacent.

Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 01/09/2013

For the Michigan Department of Natural Resources, Forest Resources Division

