

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 21 T 51N R 36W	7
	S 21 T 51N R 36W	14
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 7 05/31/2012  
14 05/31/2012 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(7-Sec. 21) North 1/16 corner between Sections 21 and 22. Not previously monumented.

(14-Sec. 21) South 1/16 corner between Sections 21-22. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(7-Sec. 21) Established the position for the corner midway and on the Section line between Section  
corner 1313.69' north and Quarter corner 1313.69' south.

(14-Sec. 21) Established the position for the corner midway and on the Section line between Section  
corner 1313.69' south and Quarter corner 1313.69' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(7) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
5" Sugar N72E 10.0' mrkd "1/16S BT"  
6" Sugar S01W 13.85' do  
6" Sugar S81W 13.7' do  
4" Sugar N08W 17.9' do  
Set sq'd Cedar post adjacent.  
Bearings are magnetic.

(14) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
4" Sugar S70E 2.4' mrkd "1/16S BT"  
5" Y.Birch S17E 9.1' do  
5" Y.Birch S72W 15.2' do  
13" Sugar N27W 34.0' do  
Set sq'd Cedar post adjacent.  
Bearings are magnetic.

Signed by Stephan J. Szyszkoski

Date 07/11/2012

Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

