

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: 07/13/2016

For corner(s) in: Houghton County

Original Public Land Survey Corner

Corner Code

b. S T 51N R 36W
 S T R
 S T R
 S T R

E02 (GCDB 300640)

Property Corner

1/16 Corner Code

a. S 5 T 51N R 36W
 S T R
 S T R
 S T R

9 (GCDB 260640)

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5	●	4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A. Corner History

a.) Center-East 1/16 corner, Section 5. Not previously monumented.

b.) Quarter corner common to Sections 4 and 5. 1985 - K.L.Sackett RLS reestablished the corner position proportionate to the original record between Section corners north (40.96 ch. R) and south (40.00 ch. R). Set 1"IDx32" I.pipe with 4" aluminum cap. 5" Sugar S07°E 5.0', 4" Sugar N26°E 10.2', 18" Spruce S60°W 19.6'.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Established the position for the corner midway and on a straight line between Center of Section 5 1300.88' west and Quarter corner E02 1300.88' east.

b.) Found the 1985 monument in good condition and at record bearing and distance from the 1985 witnesses Spruce SW and Sugar SE, both in good condition with markings visible. Accepted the monument as a careful and faithful reestablishment of the position of the original corner.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

(a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 7" Sugar N37°W 14.55' mrkd "1/16S BT"
 15" Sugar N54°E 14.9' do
 9" Sugar S85°E 18.8' do
 7" Maple S58°W 21.55' do
 Set sq'd cedar post adjacent.
 E= 7855437.331 N= 230792.385

(b.) Found 1"ID I.pipe with 4" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 21" Spruce S64°W 20.45' old blazes (1985 NBT)
 6" Sugar S07°E 5.2' scribing visible do
 7" Sugar N81°W 29.65' mrkd "1/4S NBT"
 8" Y.Birch N15°W 8.55' do
 Set sq'd cedar post adjacent.
 E= 7855833.359 N= 230773.753

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meters.
 Coordinate Reference: NGS PID RL0593, E= 7868965.488 m. N= 221669.506 m.

Stephan J. Szyszkoski

09/07/2016

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

