

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 20 T 52N R 36W	3
	S T R	(GCDB 200360)
	S 20 T 52N R 36W	10
	S T R	(GCDB 200320)
3. Miscellaneous Property in Sec.	T R	
	T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 10/28/13 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(3-Sec. 20) North 1/16 corner between Sections 19 and 20. Not previously monumented.

(10-Sec. 20) South 1/16 corner between Sections 19 and 20. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(3-Sec. 20) Established the position for the corner midway and on the Section line between Section corner 1319.93' north and Quarter corner 1319.93' south.

(10-Sec. 20) Established the position for the corner midway and on the Section line between Section corner 1319.94' south and Quarter corner 1319.94' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
7" Sugar N13°E 14.05' mrkd "1/16S BT"
5" Sugar N42°E 27.4' do
6" Sugar S27°E 26.55' do
4" Sugar N72°W 3.05' do
Set sq'd cedar post adjacent.
E= 7854337.552 N= 235974.436

(10) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Maple N49°W 21.35' mrkd "1/16S BT"
9" Maple N36°E 18.95' do
13" Maple S16°E 15.45' do
4" Balsam S25°W 10.0' do
Set sq'd cedar post adjacent.
E= 7854324.019 N= 235169.994

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).
Coord. Ref.=NGS PID RL0502: N= 234995.272 m. E= 7857774.766 m.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 11/18/2013

For the Michigan Department of Natural Resources, Forest Resources Division

