

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 25 T 52N R 36w	1
	S 25 T 52N R 36W	10
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 10 05/28/13 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(1-Sec. 25) West 1/16 corner between Sections 24 and 25. Not previously monumented.

(10-Sec. 25) South 1/16 corner between Sections 25 and 26. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(1-Sec. 25) Established the position for the corner midway and on the Section line between Section
corner 1225.18' west and Quarter corner 1225.18' east.

(10-Sec. 25) Established the position for the corner midway and on the Section line between Section
corner 1173.42' south and Quarter corner 1173.42' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(1) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
12" Sugar N43W 4.15' mrkd "1/16S BT"
9" Sugar N57E 13.8' do
6" Sugar S50E 25.7' do
4" Spruce S22W 15.55' do
Set sq'd cedar post adjacent.
E= 7861249.785 N= 234599.983

(10) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" Tamarack N02E 30.3' mrkd "1/16S BT"
3" Tamarack S65E 17.95' do
3" B.Spruce S05W 16.15' do
2" Tamarack S48W 40.75' do
Set sq'd cedar post adjacent.
E= 7860837.019 N= 233422.439

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)
Coord. Ref.=NGS PID RL0503: N= 233736.671 m. E= 7856830.966 m.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 07/30/2013

For the Michigan Department of Natural Resources, Forest Resources Division

