

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SURVEYOR'S
CERTIFICATION

For corners in
HOUGHTON
(County)

Located In:

Corner Code #

DEC 14 1998

1. Public Land Survey T 53W R 33W
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Section S _____ T _____ R _____

MEANDER-15

Seg. 1

SECTION

ROBERT F. MIKESCH 11/16/98
HOUGHTON COUNTY, REGISTER 14:46
LC 3/ 548 PAU Fee: 9.00
Page 1 of 1

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, R. W. CRAMPTON, in a field survey on OCTOBER 30, 19 98,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found
as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

MEANDER-15 NOT SET IN ORIGINAL SURVEY

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MEANDER-15, SET 1 1/4" IRON PIPE WITH 2 1/4" BRASS CAP ON LINE BETWEEN 1/4 CORNER BETWEEN SECTIONS
12 AND 13, T53N, R33W AND THE COMPUTED CORNER OF SECTIONS 12 AND 13, T53N, R33W, AND
SECTIONS 7 AND 18, T53N, R32W. WHICH WAS COMPUTED BY USING THE W 1/4 CORNER OF
SECTION 13, AS SHOWN ON THE UNRECORDED PLAT OF PORTAGE VIEW LOTS AND THE
NORTH 1/4 CORNER OF SECTION 18, T53N, R32W AND THE ABOVE STATED UNRECORDED PLAT
AT EDGE OF LARGE SWAMP. N89°44'07"E 729.70' FROM THE 1/4 CORNER BETWEEN SECTIONS
12 AND 13.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

MEANDER-15 THE 1 1/4" IRON PIPE WITH BRASS CAP WAS WITNESSED WITH SURVEY TAG NAILED TO:
6" W. BIRCH TREE N69°W 9.53', 5" W. BIRCH TREE N22°E 12.94',
6" BALSAM TREE N73°E 11.21', 16" POPLAR TREE S02°W 11.73'.



Signed by Robert W. Crampton

Date Nov. 4, 1998

Surveyor's Michigan License No. 24591