

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____ _____ _____
2. Property Controlling in Section	S 20 T 55N R 31W _____ S 20 T 55N R 31W _____ S _____ T _____ R _____	8 3 _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____ _____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4			3		2		1	
3													
4	7		8		9			10		11		12	
5													
6	18		17		16			15		14		13	
7													
8	19		20		21			22		23		24	
9													
10	30		29		28			27		26		25	
11													
12	31		32		33			34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 04/23/13 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 20) West 1/16 corner, Section 20. Not previously monumented

(3-Sec. 20) North 1/16 corner between Sections 19 and 20. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 20) Established the position for the corner midway and on a straight line between Quarter corner 1382.27' west and the Center of Sec. 20 1382.27' east. The Center of Section 20 is the intersection of 1/4 lines, the N-S 1/4 line being run from the North 1/4 corner of record at a bearing which is the weighted mean bearing of the east and west Section lines.

(3-Sec. 20) Established the position for the corner midway and on the Section line between Section corner 1317.54' north and Quarter corner 1317.54' south. The position for the corner falls approximately 15' south of the edge of a stream (2 feet of snow on the ground at this time).

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
8" B.Spruce N75°E 26.35' mrkd "1/16S BT"  
4" Maple S08°E 18.0' do  
18" W.Pine S40°W 9.8' do  
5" Balsam N12°W 7.1' do  
Set sq'd cedar post adjacent.  
E=7903582.270 N=263766.380

(3) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
6" B.Spruce S59°E 51.4' mrkd "1/16S BT"  
6" W.Pine S39°E 33.5' do  
7" B.Spruce S08°E 40.4' do  
9" W.Pine S12°W 48.2' do  
Set sq'd cedar post adjacent.  
E=7903154.525 N=264176.309

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)  
Coord. Ref.=NGS PID DL5985: N= 259878.551 m. E= 7882233.252 m.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 05/07/2013

For the Michigan Department of Natural Resources, Forest Resources Division

