## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #	
1. Public Land Survey	TR TR		5
2. Property Controlling in Section	S 30 T 55N R 32W S 30 T 55N R 32W S T R	B8 SMC E of B8	
3. Miscellaneous Property in Sec.	S T R S T R		
4. Lot No. , Red 5. Private Claims	corded Plat		Register of Deeds Stamp & File Number  A B C D E F G H I J K L M
I, Stephan J. Szyszkoski, in a field survey on SMC 07/28/2011 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with 7 the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, a			
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.			

A. Description of original monument and accessories and/or subsequent restoration:

(B8) Center of Section 19. Not previously established.

(SMC East of B8). Special Meander Corner at the intersection of the E-W 1/4 line of Section 19 with the edge of the leatherleaf and tag alder marsh, west of Portage Lake. Not previously established.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(B8) Established the corner at the intersection of the E-W 1/4 lineof Sec. 19, being a straight line between Quarter corners A8 and C8, with a straight line from Quarter corner B9 having a bearing that is parallel to the west line of Section 19.

(SMC) Established the corner on the E-W 1/4 line of Section 19, being a straight line between 1/4corners A8 and C8, at its intersection with the transition from upland to the leatherleaf and tag alder marsh on the west side of Portage Lake, 462.61' east of the monumented Center of Section 19.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(B8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 6" Hemlock N28E 19.05' mrkd "C1/4 BT" 9" Y.Birch S40E 10.35' do 12" Y.Birch S33W 3.5' do 3" Cedar N33W 25.25' do Set sq'd cedar post adjacent. Bearings are magnetic.

(SMC) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: mrkd "SMC BT"

5" Hemlock N03E 25.4' 5" Tamarack S58E 41.9'

do

9" Maple S33W 3.65'

do

9" Maple N62W 15.45'

do

Set sq'd cedar post adjacent.

Bearings are magnetic.

Date

11/17/2011

STEPHAN J SZYSZKOSKI LAND SURVEYOR

CAND

For the Michigan Department of Natural Resources, Forest Management Division

33986

16780

Surveyor's Michigan License No.

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

Revised May 14, 1975

Revised Jan., 1983 Rervised Oct., 1995