

APPROVED LAND CORNER
P.A. 74, of 1970
Houghton County

APR 30, 1999
Robert W. Coughlin

SURVEY &
REMONUMENTATION

JUL 23 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74,
Mich. P.A. 1970

For corners in

Houghton County
(County)

Located In:

Corner Code #

MARY SCHOOS 05/05/99 2
HOUGHTON COUNTY, REGISTER 15:06
LC 3/ 590 PAU Fee: 9.00
Page 1 of 1

1. Public Land Survey Section 32 T 55N R 32W C-12, 13 #22
T R (Meander Corner)
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File
Number

Corner C-12, 13 is the meander corner on the SE shore of Portage Lake, on section
line common to Section 31 & 32. T55N, R32W.

I, Michael T. Drewyor, in a field survey on December 4, 19 97 do hereby
state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines
1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree
of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Meander Corner At 4.20 chains (meas. from S), intersect Portage Lake.

Set Meander Post Var. 5° 15' E
No trees in Marsh

No evidence of original monument or accessories found. This line was originally surveyed by Deputy Surveyor William Ives between
July 13, 1845 & July 24, 1845.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Meander Corner - In 1967, Charles Hein, RLS 13034 shows this meander corner in place 214.85 feet North of the SW corner of
Section 32. Upon retracing Chuck's survey I found the shore of Portage Lake at 209.5 feet North of the SW corner of Section 32, &
also found 5/8" iron rod at grade as called for on the same line at 160 feet North. Since this point is 49.5 feet from the shore of
Portage Lake & on the section line it was witnessed as the meander corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

All witness points in trees are PK nails and washers.

Meander Corner - Found 5/8" iron rod (description above).

Witnesses:

N 43° E, 17.72 ft., SW Corner Frame Shed
S 09° E, 36.45 ft., 7" White Birch
S 74° W, 18.23 ft., 7" White Birch
N 40° W, 20.19 ft., 4" Tag Alder

Signed by Michael T. Drewyor
Surveyor's Michigan License No. 24245

Date April 13, 1999



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

By: Hitch, Inc., P.C., Houghton, MI
Job No. 97012

REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

Corner, C-12, 13
Meander Corner #22