

JAN 19 2001

2000 REMONUMENTATION

Re-Monumented 2, Page 85

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Huron

(County)

Located in:

Corner Code #

- | | | | |
|------------------------------------|---------|-----------|------|
| 1. Public Land Survey | Sherman | T15N R16E | A-12 |
| | | T R | |
| | | T R | |
| | | T R | |
| 2. Property Controlling in Section | S | T R | |
| | S | T R | |
| 3. Miscellaneous Property in Sec. | S | T R | |
| | S | T R | |

STATE OF MICHIGAN
HURON COUNTY
RECORDED

20 SEP 2000 2:07 PM

FRANCES L. HOLDWICK
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Charles S. Getz, in a field survey on May 10, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

A-12 1834 G.L.O., H. Parke D.S. County Road Commission Records - Iron Pin

Set quarter section post

Beech 10", N11 $\frac{1}{2}$ °W, 22 Links

Hemlock 7", S25°W, 25 Links

Recorded Surveys - NONE

L.C.R.C. - NONE

Unrecorded Surveys - Brown, 12-29-99, 5/8" Steel Stake

County Surveyor Records -
NONE

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-12

W 1/4 Cor, Section 31, T15N-R16E

Found 3/4" Pipe

Accepted as the best available evidence

of the original corner position

(On Edwards Road)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-12

W 1/4 Cor, Section 31, T15N-R16E

Found 3/4" Pipe

N50°E 44.0' to Wooden Telephone Post with Box

S30°E 88.0' to Nail in Power Pole

N85°E 27.2' to South End of C.M.P.

N45°E 39.0' to North End of C.M.P.

South 2630.33' to SW Cor, Sec 31, T15N-R16E

North 2629.38' to NW Cor, Sec 31, T15N-R16E



Signed by Charles S. Getz

Date June 3, 2000

Surveyor's Michigan License No. 25843

PEER GROUP APPROVED AT MEETING

HELD September 18, 2000. RLB