

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

Re-Mon Leber 2, Page 92

**Huron**  
(County)

**Corner Code #**

STATE OF MICHIGAN  
HURON COUNTY  
RECORDED

29 NOV 2000 11:21 AM

FRANCES L. HOLDWICK  
REGISTER OF DEEDS

**Register of Deeds Stamp & File Number**

1. Public Land survey: **Sebewaing** T 15\_N R 9\_E A-11 ✓  
T \_\_\_\_\_ R \_\_\_\_\_ A-12  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_
2. Property Controlling S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
in Section S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_
3. Miscellaneous S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
Property in Sec. S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_
4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_
- SURVEY &  
MONUMENTAL  
JAN 19 2001  
SECTION

[illegible]

A. Description of original monument and accessories and/or subsequent restoration:  
Original survey, West Bdy. T15NR9E, 1835, Harvey  
Parke D.S.

A-12 West 1/4 Corner of Section 31  
Not monumented

County Surveyor's Record: none  
Recorded Surveys: none  
LCRC: none

County Surveyor's Record: none  
Recorded Surveys: none  
LCRC: none

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

**A-11 Corner of Sections 30, 31**

A-12 West 1/4 Corner of Section 31

Found no evidence of the original corner position  
Set 4" iron at proportionate distance between M-9 & M10, T15NRSE on West shoulder of Michigan Highway M-25 Centerline of Bach Road bears East

Found no evidence of the original corner position  
Chisled '+' in concrete at proportionate distance between M-10 & M-11, T15NR8E

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-11 Corner of Sections 30, 31  
1/2" iron w/cap #39089

A-12 West ¼ Corner of Section 31  
¼" iron w/cap #39089 in mon box  
From which:


4" iron bears N0°W, 87.33'  
Tag in power pole bears S65°W, 54.3'  
+ Brass Cap bears N85°W, 14.4'  
+ Top of conc ROW bears N37°W, 131.8'  
M-9, Corner of Sections 24 & 25, T15NR8E  
bears N0°00'00"E, 78.77'  
M-10, East 4 corner of Section 25,  
T15NR8E bears S0°00'00"W, 2546.81'

FROM WHICH.  
1/2" iron bears N20°E, 90.4'  
Tag in wood post bears S70°E, 64.4'  
Chisled 'x' bears N35°W, 110.2'  
Chisled 'x' bears N25°W, 152.8'  
M-10, East 1/4 corner of Section 25, T15NR8E  
bears N0°00'00"E, 94.52'  
M-11, Corner of Sections 25 & 36, T15NR8E bears  
N0°00'00"E, 2531.06'

Signed by \_\_\_\_\_

Surveyor's Michigan License No. 39089

APPROVED AT PEER BOARD MEETING 11-02-06 RLB



2000

MICHIGAN BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995