

ACCEPTED BY THE HILLSDALE COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 245 OF 1990 AS A MEETING HELD ON 11-25-98 AL RINGENBERG, CO. REC.

LIBER 3 PAGE 278

12019 HILLSDALE CO. MICH. 98.NOV 25 AM 10 02

HILLSDALE COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Hillsdale (County) Located In: Corner Code #

1. Public Land Survey T6 S R4 W C-11

2. Property Controlling in Section S T R

3. Miscellaneous Property in Sec. S T R

4. Lot No. , Recorded Plat

5. Private Claims

SURVEY & RECORDS REMONUMENTATION FEB 23 1999 SECTION Register of Deeds Stamp & File Number

I, Frederick J. Cutcher, in a field survey on October 26, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. by Wm. Brookfield, 1825: Black Ash 7" N. 54-1/2° E. 12 lks; Swamp White Oak 15" North 10 lks.

No other information available.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set corner in centerline of E/W road in line with centerline of road to North and in line with remains of old fence to South.

No witnesses were found.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" x 30" iron with county remonumentation cap in monument box and is accepted as the best available evidence of the position of the original corner.

In centerline of E/W road in line with remains of fence to South and in line with centerline of road to North and is in accordance with fence (1/16) to North running East.

Top cen. E. end CMP South 27.0'
Set nail & spotter W. side 18" Oak S 35° E. 46.65'
Set nail & spotter W. side 18" oak S. 20° E. 46.72'
Steel post at E. end guard rail S. side road S. 85° W. 137.7' (face)
Stop sign N. 15° W. 61.55' (face)

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by Frederick J. Cutcher Date 11/4/98

Surveyor's Michigan License No. 24592

