

12401

RECORDED

HILLSDALE CO. MICH.

'98 DEC 4 AM 11 47

ACCEPTED BY THE  
SURVEY PEER GROUP AS THE  
CORNER UNDER MICHIGAN PUBLIC ACT 74  
OF 1970. AN AGA MEETING HELD ON  
AL RINGENBERG, CO. REP

LIBER 3 PAGE 299

REMONUMENTATION

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

## 1. Public Land Survey

T 7S R 1W B-7

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

## 3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Jeffrey A. Bieszk, in a field survey on 25 Nov, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

## A. Description of original monument and accessories and/or subsequent restoration:

GLO

Post

12" Beech S12E 16 lks

24" W. Wood N86W 50 lks

LCRC L1 P515 Russell Cole

Found Stone Set R.R. Spike

8" Basswood NE 28.90 ft.

36" Ash NNE 31.14 ft.

24" Hickory SE 37.62 ft.

LCRC L1 P602 Alan Ringenburg

Found R.R. Spike

36" Ash N40E 31.07 ft.

8" Basswood N60E 28.62 ft..

24" Hickory S25E 37.32 ft

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Railroad Spike as set by Cole and re-witnessed by Ringenburg, dug and found stone as in Cole LCRC. Accepted as the best available evidence to the position of the original corner.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box

Nail &amp; Tag 28" Hickory S30E 36.84 ft.

Nail &amp; Tag Fence Post S88E 28.04 ft.

Nail &amp; Tag 6" Cedar S18W 29.79 ft.

Nail &amp; Tag 4" Hickory N20E 30.50 ft.

SURVEY &  
REMONUMENTATION

FEB 23 1999

SECTION  
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by \_\_\_\_\_  
Surveyor's Michigan License No. 41093

Date 4 December 1998