

HILLSDALE COUNTY REMONUMENTATION PROGRAM

RECORDED
HILLSDALE CO. MICH.LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

0 SEP 14 AM 11:38



For corners in

HILLSDALE COUNTY
READING TWP

Located In:

Corner Code #

1. Public Land Survey T 7 S R 4 W C-5
 T R
 T R
 T R
2. Property Controlling S T R
 in Section S
 T R
3. Miscellaneous S
 T R
 Property in Sec. S
 T R

4. Lot No. , Recorded Plat

5. Private Claims

I, EDWARD W. REED, in a field survey on AUGUST 16, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 7, 8, 17 AND 18

A. Description of original monument and accessories and/or subsequent restoration:

1825: CORNER SET

1973: AJ HATT: FD 12" STONE SURROUNDED BY STONES AND BRICK WITH WOOD STAKE
SET 1/2" IRON ROD OVER STONE RECORDED IN LCRC # 1490

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON, GRANITE STONE AND REMAINS OF WOOD AS DESCRIBED BY HATT
REMOVED STONE TO SET 3/4" x 30" REBAR IN CAST IRON MONUMENT BOX

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3/4" x 30" REBAR IRON WITH REMON CAP IN CAST IRON MONUMENT BOX 4" BELOW GRAVEL ROAD SURFACE.

NAIL E. SIDE 42" MAPLE S20W 70.33'
 NAIL SW SIDE 20" WALNUT S45E 46.26'
 NAIL NW SIDE, 32" MAPLE N75E 36.05'
 NAIL N. SIDE 18" WALNUT S60W 43.38'
 SE CORNER OF TELEPHONE PED N40E 50.25'
 IRON N60E 5.3'

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION
OF THE POSITION OF THE ORIGINAL CORNER

Signed by

EDWARD W. REED

DATED: AUGUST 16, 2000

Surveyor's Michigan License No. 33985

SURVEY &
EMONUMENTATION

JAN 12 2001

SECTION
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

