



034942

RECORDED  
HILLSDALE CO. MICH.

00 OCT 11 AM 10:31

LIBER 5 PAGE 24

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 8S R 1W G-11

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

SURVEY &  
REMONUMENTATION

JAN 12 2001

SECTION

Register of Deeds Stamp &amp; File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Jeffrey A. Bieszk, in a field survey on 6 Oct. 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5		4		3		2		1		
3												
4	7	8		9		10		11		12		
5												
6	19	17		16		15		14		13		
7												
8	19	20		21		22		23		24		
9												
10	30	29		28		27		26		25		
11												
12	31	32		33		34		35		36		
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Ziba Swan (1824)  
18" Beech N40E 6 lks  
30" Beech S16E 22 lks

Geo Mark (1869) survey #512  
Stone 25x11x10 Earthen, Brick  
Geo. Mark (1876) survey #734 &  
#735, re-established stone & brick  
stone N45E 70.75 lks  
stone S45W 70.75 lks

Glenn E. Richards LCRC L1-P611  
Found R.R Spike  
SW tele. Pedastal N45W 47.12 ft.  
Nail & disk 24" Walnut N50W 57.05 ft.  
Nail & disk E.P. N20E 158.75 ft.  
Nail & disk E.P. S40E 70.08 ft.  
Nail & disk T.P. S25W 90.75 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Glenn Richard found R.R. spike which checked with witnesses he got from Alan Ringenberg dated 6/21/78. I found R.R. spike as witnessed by Richards, dug under and found no stone. R.R. spike was 3 feet North and 1 foot East of intersection of Roads. Accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box

Stop sign S 80 W 69.18 ft.

Stop sign N 80 E 56.83 ft.

Nail w/tag 18" Walnut N 65 W 57.96 ft.

Nail w/tag Power Pole S 45 E 69.66 ft.



Signed by

Surveyor's Michigan License No.

41093

Date

October 11, 2000