



REMONUMENTATION

LIBER 3 PAGE 338

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

025220

For corners in

HILLSDALE

(County)

Located in:

Corner Code #

1. Public Land Survey

T8S R 2W E-9

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

RECORDED
HILLSDALE CO. MICH.

NOV 29 AM 9:16

HILLSDALE CO. MICH.

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Jeffrey A. Bieszk, in a field survey on 25 Oct., 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Wm. Brookfield. (1825)

13" R. Oak N52.5W 24 lks.

11" W. Oak S70.5W 40 lks.

Survey Geo. Mark Co. Surveyor

Survey No. 620

Iron bolt

12" B. Walnut S24.75W 112 lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found iron in monument box. This iron fits the maps for highway M-99. Found no other information, accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box

North Leg Stop Sign S 75 W 53.97 ft

South Leg Stop Sign N 65 E 51.48 ft.

Nail w/tag Power Pole N 35 W 109.94 ft.

Nail w/tag Power Pole N 45 E 136.75 ft.

Signed by [Signature]Date 24 November 1999Surveyor's Michigan License No. 41093