

034010

RECORDED
HILLSDALE CO. MICH.

00 SEP 14 AM 11:36

Judy Canfield
REG. OF DEEDS

HILLSDALE COUNTY REMONUMENTATION PROGRAM

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE COUNTY Located In: _____ Corner Code #
RANSOM TWP

1. Public Land Survey T 8 S R 2 W E-5
 T _____ R _____
 T _____ R _____
 T _____ R _____

2. Property Controlling in Section S _____ T _____ R _____
 S _____
 T _____ R _____

3. Miscellaneous S _____
 T _____ R _____
 Property in Sec. S _____
 T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, EDWARD W. REED, in a field survey on AUGUST 17, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 8, 9, 16 AND 17

A. Description of original monument and accessories and/or subsequent restoration:

1825: CORNER SET
 1957: MSHD - FIELD NOTES INDICATED 1 1/4" IRON PIPE AND WITNESSES

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD SET IN CONCRETE IN CAST IRON MONUMENT BOX
 REMOVED 1/2" IRON, SET 3/4" x 30" REBAR WITH REMON CAP IN CAST IRON MONUMENT BOX

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

TAG IN EAST SIDE OF POWER POLE	S17°W	296.01'
NW CORNER HOUSE	S42°W	261.02'
TOP CENTER OF TELEPHONE PEDESTAL	N75°W	178.32'
TOP CENTER OF WEST END OF CONCRETE CULVERT	N18°W	109.55'
TOP CENTER OF EAST END OF CONCRETE CULVERT	N27°E	106.80'
TAG SOUTH SIDE OF POWER POLE	N76°E	129.50'

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

EDWARD W. REED

Surveyor's Michigan License No. 33985

DATED: AUGUST 17, 2000

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	18	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

