

034011

RECORDED
HILLSDALE CO MICH.

00 SEP 14 AM 11:36

Judy VanZandt
REG. OF DEEDS

LIBER 5 PAGE 8
HILLSDALE COUNTY REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE COUNTY
RANSOM TWP

Located In:

Corner Code #

1. Public Land Survey

T 8 S R 2 W

G-5

T R

T R

T R

2. Property Controlling
in Section

S T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, EDWARD W. REED, in a field survey on AUGUST 18, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 9, 10, 15 AND 16

A. Description of original monument and accessories and/or subsequent restoration:

1825: GLO CORNER SET

1867: GEO MARK - STONE

1977: D. OLMSTEAD - STONE GONE, RESET CORNER FROM MARK'S SURVEY.

SET 3/4" x 30" STEEL AXLE, RECORDED IN LCRC # 6560 LIBER 1, PAGE 554

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND SOLID AXLE FITTING WITNESS OF LCRC # 6560

SET 3/4" x 30" REBAR WITH REMON CAP IN CAST IRON MONUMENT BOX FLUSH WITH PAVED ROAD SURFACE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

TAG IN NORTH SIDE OF POWER POLE	S73°E	132.45'
CONCRETE POST	N32°E	44.1'
TELEPHONE PEDESTAL	N34°E	38.82'
TAG IN NORTH SIDE OF POWER POLE	S51°W	39.05'
TAG TOP CENTER OF WOOD POST	S88°W	34.02'
TAG TOP CENTER OF WOOD POST	N27°W	62.62'

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

EDWARD W. REED

Surveyor's Michigan License No. 33985

DATED: AUGUST 18, 2000

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

