

034012

RECORDED
HILLSDALE CO. MICH.

00 SEP 14 AM 11:36

Judy Vanfossen
REG. OF DEEDS

LIBER 5 PAGE 9
HILLSDALE COUNTY REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE COUNTY
RANSOM TWP

Located In:

Corner Code #

1. Public Land Survey T 8 S R 2 W H-5
T R
T R
T R
2. Property Controlling S T R
in Section S
T R
3. Miscellaneous S
T R
Property in Sec. S
T R

4. Lot No. , Recorded Plat

5. Private Claims

I, EDWARD W. REED, in a field survey on AUGUST 15, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

QUARTER CORNER COMMON TO SECTIONS 10 AND 15, RANSOM TOWNSHIP, HILLSDALE COUNTY, MICHIGAN

A. Description of original monument and accessories and/or subsequent restoration:

1825: SET CORNER

1867: GEO. MARKS - STONE, STAKE, EARTHEN

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

RAN TRAVERSE BETWEEN CORNERS EAST AND WEST, AT MID POINT, FOUND MAG NAIL, FOUND NOTHING ELSE
ACCEPTED MIDPOINT

SET 3/4" X 30" REBAR IRON WITH REMON CAP IN CAST IRON MONUMENT BOX FLUSH WITH PAVED ROAD SURFACE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


3/4" X 30" REBAR IRON WITH REMON CAP IN CAST IRON MONUMENT BOX FLUSH WITH PAVED ROAD SURFACE
NAIL & TAG WEST SIDE OF 24" WALNUT N10E 28.30'
NAIL & TAG TOP CENTER OF WOOD POST SOUTH 30.28'
NAIL & TAG TOP CENTER WOOD POST N70E 58.20'
6" FIR S57W 41.4'
CENTERLINE OF E-W ROAD SOUTH 2.5'

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT
OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Edward W. Reed
EDWARD W. REED

Surveyor's Michigan License No. 33985

DATED AUGUST 15, 2000



	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	10		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													