

034014

RECORDED
HILLSDALE CO. MICH.

00 SEP 14 AM 11:36



HILLSDALE COUNTY REMONUMENTATION PROGRAM

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

John Vanjones
REG. OF DEEDS

For corners in

HILLSDALE COUNTY Located In: Corner Code #
RANSOM TWP

1. Public Land Survey T 8 S R 2 W J-5
T R
T R
T R
2. Property Controlling S T R
in Section S
T R
3. Miscellaneous S
T R
- Property in Sec. S
T R

SURVEY &
REMONUMENTATION

JAN 12 2001

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat 5. Private Claims

I, EDWARD W. REED, in a field survey on AUGUST 18, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

QUARTER CORNER COMMON TO SECTIONS 11 AND 14.

A. Description of original monument and accessories and/or subsequent restoration:

1825: GLO CORNER SET

1895: GEO MARKS STONE, STAKE AND EARTHEN

1979: W. SOMMER: RESET CORNER FROM SURVEY BY GEO MARKS, SET RAIL ROAD SPIKE
AT CORNER, RECORDED LCRC # 863. LIBER 1, PAGE 595

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND RAILROAD SPIKE FITTING WITNESSES OF LCRC # 863

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 3/4" x 30" REBAR WITH REMON CAP IN PLACE OF RAIL ROAD SPIKE IN CAST IRON BOX FLUSH WITH PAVED ROAD
SOUTHWEST CORNER OF CONCRETE HEADWALL S30°W 18.37'
NAIL IN POWER POLE S40°E 35.92'
TELEPHONE PEDESTAL S80°W 108.9'
CENTERLINE OF EAST-WEST ROAD NORTH 1'

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT
OF THE POSITION OF THE ORIGINAL CORNER.

Signed by *Edward W. Reed*
EDWARD W. REED

DATED: AUGUST 18, 2000

Surveyor's Michigan License No. 33985

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

