

FEB 22 1996

COMMISSION

950002191 Liber 8

Page 503

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

INGHAM

(County)

Located in:

Corner Code #

ALAIEDON TOWNSHIP

#001

1. Public Land Survey

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

2. Property Controlling  
in Section

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

3. Miscellaneous

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

Property in Section 34

S \_\_\_\_\_ T 34 R 1W

MISC. #7

FILED

11/07/1995 09:05:04  
REGISTER OF DEEDS  
PAULA JOHNSON  
INGHAM COUNTY, MI

Register of Deeds Stamp &amp; File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, DAVID R. LOHR, in a field survey on JUNE 7, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumiented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

MISC. #7:

1. CORNER NOT SET IN ORIGINAL GOVERNMENT SURVEY:

2. SURVEY BY ANSON JACKSON, COUNTY SURVEYOR, 9/12/1845, RECORDED IN VOL. 4, PAGE 57, NO MENTION OF MONUMENT, WITNESSED BY:

B. ASH 10" N 89 E 39 LINKS (25.74')

TAM. 8" N 36 W 11 LINKS (7.26')

CONTINUED ON BACK

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MISC. #7:

VISITED APPARENT LOCATION OF CORNER AND DETECTED OBJECT WITH METAL DETECTOR. EXCAVATED AND FOUND 1 3/4" X 3/4" BENT PIPE AT DEPTH OF 6". LOCATED BASE OF BENT PIPE TO NORTHEAST AND SET 1/2" X 24" REBAR OVER IT. CORNER FALLS 3 FT. WEST OF CENTERLINE OF WOLVERINE ROAD AND ON FENCELINE TO EAST. MEASURED NORTH TO STONE/CROCKERY AT I-11, 1326.82 FT. AND SOUTH TO I-12, 1326.64 FT. CORNER FALLS 0.31 FT. WEST OF TRUE LINE NORTH AND SOUTH. ACCEPTED LOCATION OF PIPE AS THAT CALLED FOR IN ITEM #A-3 AND A-4, BASED ON WITNESS TO 42" OAK EAST AS THAT OF THE 2" OAK IN ITEMS A-3 AND A-4.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

MISC.#7: SET 1/2" X 24" REBAR/CAP #30090 3 FEET WEST C/L OF WOLVERINE ROAD ON FENCE TO EAST: WITNESSED BY:

SET N&amp;T #30090 N/S 42" OAK

AZ. 84-10-00 27.82'

SET N&amp;T #30090 SW/S 5" CHERRY

AZ. 126-28-00 36.10'

SET N&amp;T #30090 N/S 6" MAPLE

AZ. 248-33-00 61.15'

SET N&amp;T #30090 NE/S 22" MAPLE

AZ. 326-58-00 50.15'

BEARING AND DISTANCE NORTH TO I-11

AZ. 01-10-28 1326.82'

BEARING AND DISTANCE SOUTH TO I-12

AZ. 181-08-46 1326.64'



Signed by

David R. Lohr

Date

11-1-95

Surveyor's Michigan License No.

30090

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

P.A. 345 INGHAM COUNTY

DEED APPROVED: 10/24/95 AL

3. SURVEY BY W.A. ROWE, COUNTY SURVEYOR, DATED 3/14/1896, RECORDED IN VOL 2, PAGE 250, STATES: "STONE-GAS PIPE" ... SET BY ROWE IN A FORMER SURVEY, WITNESSED BY:  
W. OAK 2" N 89 E, 42 1/2 LINKS (28.05')  
HICK. 4" S 6 1/2 E, 209 1/2 LINKS (138.27')  
SHOWS NO DISTANCE NORTH OR SOUTH
4. SURVEY BY W.A. ROWE, COUNTY SURVEYOR, DATED 3/31/1896, RECORDED IN VOL 2, PAGE 249, STATES: "GAS PIPE-STONE ON TOP" WITNESSED BY:  
HICK. 4" SOUTH 6 1/2 DEGREES EAST, 209 1/2 LINKS (138.27')  
W. OAK 24" NORTH 28 DEGREES EAST, 182 LINKS (120.12')  
W. OAK 2" NORTH 89 DEGREES EAST, 42 1/2 LINKS (28.05')  
SHOWS DISTANCE NORTH TO I-11 OF 20.065 CH. (1324.29')  
SHOWS DISTANCE SOUTH TO I-12 OF 20.065 CH. (1324.29')