

SURVEY &
REMONUMENTATION

APR 27 1995

COMMISSION

IOSCO COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
IOSCO COUNTY
FILED

5 DEC 94 1:55 P.M.

BONITA M. COYLE
REGISTER OF DEEDS

94-25

Register of Deeds Stamp & File Number

For corners in

Iosco
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 22N R 8E

K-7 to L-7

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

No. 5

4. Lot No. , Recorded Plat

5. Private Claims

I, James H. Granger, in a field survey on September, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

1843' Original Survey
John Mullett

Set Wood Post
12" Yellow-Pine N25°W 31 lks
12" Yellow-Pine S53°W 60 lks

1937 Sub'd.

Pinehurst (1" Pipe)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Search could not locate 1" pipe. Located several sub'd monuments to establish
Sec. line. Located cor. K-7 and extended Sec. line. record distance. Found ½"
iron in approx. location of corner. Accepted ½" iron position.

ACCEPTED BY THE IOSCO COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 11-10-94

James H. Granger

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 30" rebar with alum cap

N85°W 28.28' Set tag in 6" Ash
N75°W 24.20' Set tag in 5" Birch
West 215.83' conc. mon.
East 37.11' ½" capped iron (#16050)



Signed by James H. Granger

Date November 10, 1994

Surveyor's Michigan License No. 16041