

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 4 T 41N R 31W	9
	S T R	(GCDB 360640)
	S 4 T 41N R 31W	13
	S T R	(GCDB 360620)
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 01/21/16 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 4) Center-East 1/16 corner, Section 4. Not previously monumented.

(13-Sec. 4) Southeast 1/16 corner, Section 4. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 4) Established the position for the corner midway and on a straight line between Quarter
corner 1322.03' east and the intersection of 1/4 lines of Section 4 1322.03' west.

(13-Sec. 4) Established the position for the corner at the intersection of straight lines connecting
opposite 1/16 corners, those to the north, east, and west being monumented.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Poplar S75°E 4.8' mrkd "1/16S BT"
4" Poplar S24°W 9.65' do
6" Poplar N70°W 10.85' do
2" Ash N31°W 17.65' do
Set sq'd cedar post adjacent.
E= 7908197.599 N= 133530.621

(13) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Y.Birch N80°E 15.25' mrkd "1/16 S BT"
9" Y.Birch S02°W 16.75' do
7" Maple S54°W 18.6' do
7" Maple N27°W 11.8' do
Sq'd cedar post adjacent.
E= 7908190.544 N= 133124.061

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.
Coord. Ref.=NGS PID RL0240: N= 145070.966 m. E= 7907633.632 m.

Signed by Stephan J. Szyszkoski Date 02/25/2016
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division