SURVEY & REMONUMENTATION

FEB 21 2001

COMMENCING YEAR 2000 RECEIVED FOR RECORD IRON COUNTY, MICHIGAN

1 ED 2 1 2001				nn	DEC -5	PM 12	: 49		
	LAND CORNER	RECORDATION CE	RTIFICATI	E / ().	156 -3	10:10	l. 8,	P. a	202
SECTION For corners in	Filing Require	ment of Act 74, Mich.	P.A. 1970) ~ (1	f.	,		
rot comers in				4	Delice of	as the	lie		
lron	Located In:	Corner Code #	İ	¥:	metan zin	中戶 學問	06		
(County)		. Or as too.							
1. Public Land Survey	T 42N R 31W	G-1 V							
	T <u>43N</u> R <u>31W</u> T R	G-13							
	TB								
2. Property Controlling S	_ TR								
in Section S 3. Miscellaneous S	_ <u>T R</u>	•							
Property in Sec. S	- TR T R			Regis	ter of De	eds Sta	mp & Fi	le Nur	nber
, ,									
4 Lot No Popurdad	Dĺo+								
4. Lot No, Recorded 5. Private Claims				1 A B	C D E	F G	H I	JK	L M
				2 6-		- 4	- 3	- 2	
				3			++	+	
I, Robert A. Goodreau in a field sur	vey on May 9, ;	20_00 do hereby state tha	t under	4 7-		- إ- وٰ	-1'0	-11	12
requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey				5	1 1 1	++		++	
instructions of the United States Department of the Interior, Bureau of Land Management or by a				6 -18-		-1'6	-15	-14	-13-
decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of				7			1		
Law; established, re-established, monume			Jourt Of	819-	1-20-	-21	-22	-23	-24
NOTE: Not more than 2 comers, a	all in the same town ar	d range, may be recorde	d on this	10 30-	29	-28	27	26-	-25
certificate.		,		11	111	1 +	Ī.	11	Ī.
		•		12 -31-	32	_33	-34-	-35	-36-
				13					
A. Description of original monumer	it and accessories and/	or subsequent restoration	on:						
G-1/G-13 Original corner establ 1846.	ished by John Burt, U.	S. Deputy Surveyor, on	30 July						
Original witnesses: Ceda	ar 7 N12E 18	links							
	ne 22 N22W 18 I		•						
1" iron pipe w/ 4" aluminu (Liber 2, Page 512).	m cap placed by Frank	J. Bray RLS, from 4 orig	ginal bearin	g trees, o	on 1 Dece	mber 1	967		
B. Description of corner evidence	found and/or method ε	applied in restoring or ree	establishing	corner:					
G-1/G-13 Found corner as descr		.,	·						
G-17G-10 Galla come: as aescr	ibed by bray								
Found witness recorded as:	22" red pine (S34	1)(N.B.T.) N 87° E, 148	8 links		PEER,	3ROUP	APPR	OVEC)
				TRO	1 Say	y Fest	N //-	4-20	00
Corner record research on file	with county representat	ive.			COUNT	Y REF	PRESENT	TATIVE	
C. Description of monument for	corner and accessories	s established to perpetua	ate locating	the posi	tion of th	e corne	r:		
G-1/G-13 Accepted monument	as found								
a 170 to Accopted Monament	so round.								
Witnesses: 23" red pine N	190° E, 98.75' 46° E, 29.22' (NBT)	Note: Measureme	ents taken	to a nail i	n side of	witness	ies.		
•	90° W, 11.20' (NBT)				Š	INE OF	MICH	11/2	
5.5" spruce S 10° W, 50.87' (NBT) sign post 1' North					. 0	ROB	ERT A.	72 =	
sign post 1. Ni	JI (II				.☆	PROPER	DREAU SOICHAL	\\\\\	<u>:</u>
					= 6	RUB	MEACH!	JE S	;
Signed by	1	Date	July 1,	2000	LIGHT			F. 3	
Surveyor's Michigan License No.	43053		OUIY 1,			I POFE	BEION	1160	•
odiveyor a iviidingan License No	40000					-4111	mm,		