

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

COMMENCING YEAR 2000
RECEIVED FOR RECORD
IRON COUNTY, MICHIGAN

00 DEC -5 PM12:49
L.C. Records: L. S. P. 2007
Robert A. Goodreau
REGISTER OF DEEDS

For corners in

Iron	Located In:	Corner Code #
(County)		
1. Public Land Survey	T <u>42N</u> R <u>31W</u>	<u>I-2</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Robert A. Goodreau in a field survey on May 25, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3	●	2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

I-2 Original corner: Sugar post

Original witnesses: W. Pine 24 N24W 30 links
W. Pine 30 S44E 35 links

1" ID iron pipe w/ 3.5" State of Michigan aluminum cap set proportionately on line by Arthur O. Enger RLS between Sec. Cor. 40.274 ch. S and Sec. Cor. 39.599 ch. N on 3 June 1974 (Liber 1, Page 353).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-2 Found corner as described by Enger

Found witnesses recorded by Enger as: Aspen 11 S64E (mag.) 13.0 ft. "1/4S, NBT"
Aspen 10 N17E (mag.) 34.8 ft. "1/4S, NBT"

Corner record research on file with county representative.

PEER GROUP APPROVED

Ken Ray, Ron 11-14-2000
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-2 Accepted corner as found.

Witnesses: 12" Aspen N 22° E 35.10'
10" J. Pine N 57° E 24.89' (NBT)
14" Aspen S 59° E 13.42'
11" J. Pine S 11° W 31.12' (NBT)
Sign post North 1'

Note: Measurements taken to a nail in side of witnesses.

Signed by RA. G.
Surveyor's Michigan License No. 43053

Date July 1, 2000

