

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 33 T 42N R 33W S _____ T _____ R _____ S _____ T _____ R _____	PCC East of F12
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Armstrong Ck.

I, Stephan J. Szyszkoski, in a field survey on 10/27/2011 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(PCC East of F12) Not previously established. A point on the East-West 1/4 line of Section 33 on the
west side of Armstrong Creek, being a Traverse Point at the end of a Traverse Line along the creek as
shown on a Certificate of Survey by the undersigned, dated November 3, 2011.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(PCC East of F12) Established the position for the corner on a straight line between 1/16 corner #9,
Sec. 33, monumented in 1972 by Wm.R.Donnan RLS 17618 (shown on a Certificate of Survey rec. in Liber
1 of Surveys, Page 2-5E) and the monumented Quarter corner G12, recorded in L.7 of LCR, P.70, Iron
County Records. The corner is 74' west of the water's edge of Armstrong Creek (as measured on a
perpendicular to the thread of the creek), 230.18' West of Quarter Corner G12, and 1065.54' east of a
4" sq. concrete monument at 1/16 corner #9, Sec. 33.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(PCC) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" Maple S08W 14.3' mrkd "PCC BT"
6" W.Spruce N76W 26.2' do
9" Maple N67W 31.9' do
Found an iron fence post N69W 8.7'
Set sq'd cedar post adjacent.
Bearings are magnetic.



Signed by Stephan J. Szyszkoski Date 12/27/2011
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Management Division