

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 24 T 42N R 34W	3
	S T R	(GCDB 600360)
	S 24 T 42N R 34W	4
3. Miscellaneous Property in Sec.	S T R	(GCDB 620360)
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 05/07/14 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(3) North 1/16 corner between Sections 23 and 24. Not previously monumented.

(4) Northwest 1/16 corner, Section 24. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(3) Established the position for the corner midway and on the Section line between Section corner
1321.21' north and Quarter corner 1321.21' south. The pipe leans slightly south due to subsurface
rock but the center of the cap marks the corner position.

(4) Established the position for the corner at the intersection of straight lines connecting
opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
9" Sugar N19°W 26.6' mrkd "1/16S BT"
7" Sugar N52°E 21.15' do
5" Sugar S10°E 15.8' do
9" Sugar West 31.6' do
Set sq'd cedar post adjacent.
E= 7882872.827 N= 139213.326

(4) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Sugar S55°E 30.05' mrkd "1/16S BT"
9" Sugar S08°W 11.15' do
7" Sugar S86°W 30.95' do
4" Sugar N06°W 12.1' do
Set sq'd cedar post adjacent.
E= 7883275.861 N= 139202.475

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).
Coord. Ref.=NGS PID DI0209: N= 145460.522 m. E= 7873677.972 m.

Signed by Stephan J. Szyszkoski Date 07/16/2014
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

