

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 23 T 42N R 34W	SMC N. of #6 (GCDB 560374)
	S _____ T _____ R _____	6
3. Miscellaneous Property in Sec.	S 23 T 42N R 34W	(GCDB 560360)
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 07/01/14 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(SMC) Special Meander Corner (S.M.C.) on the South shore of Minnie Lake at its intersection with the  
East 1/16 line of Section 23. Not previously monumented.

(6) Northeast 1/16 corner, Section 23. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(SMC) Established a WITNESS CORNER to the S.M.C. on the East 1/16 line at its intersection with  
south shore of Minnie Lake. As the ordinary high water mark of Minnie Lake was not determined at  
this time, the distance from the W.C. to the S.M.C. is not known. The W.C. monument is 841.95'  
north of monumented 1/16 corner #6 of Section 23.

(6) Established the position for the corner at the intersection of the North and East 1/16 lines of  
Section 23. The North 1/16 line is a straight line between 1/16 corners #5 and #7, the direction of  
the East 1/16 line is the weighted mean bearing of the N-S 1/4 line and the East line of Section 23.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(SMC) Set 1"IDx28" I.pipe with 2" alum. MDNR cap for  
a WITNESS CORNER to the S.M.C.  
Set measuring nail with MDNR tag in the side of:  
7" Tamarack N36°E 5.55' mrkd "SMC BT"  
4" Maple S28°E 9.5' do  
7" Tamarack S33°W 5.25' do  
5" Cedar N55°W 17.55' do  
Set sq'd cedar post adjacent.  
E= 7882478.519 N= 139473.448

(6) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
6" Sugar N21°W 22.2' mrkd "1/16S BT"  
9" Sugar S84°W 27.35' do  
9" Sugar S10°E 38.4' do  
3" Basswood in clump S81°E 25.25' do  
Set sq'd cedar post adjacent.  
E= 7882470.180 N= 139216.998

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum  
Coord. Ref.=NGS PID DI0209: N= 145460.522 m. E= 7873677.972 m.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 07/16/2014

For the Michigan Department of Natural Resources, Forest Resources Division

