

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Form with fields for Iron (County), Located In, Corner Code #, and sections 1-5 for Public Land Survey, Property Controlling in Section, Miscellaneous Property in Sec., Lot No., and Private Claims.

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for recording deed stamps and file numbers.

I, Stephan J. Szyszkoski, in a field survey on 07/08/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(11-Sec. 11) Southwest 1/16 corner, Section 11, also being the NE corner of Government Lot 4 and the NW corner of Government Lot 5, Sec. 11. Not previously monumented.
(SMC) Witness corner to the Special Meander (WCSMC) corner on the West shore of Bass Lake at it's intersection with the south line of Government Lot 3. Not previously monumented

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(11-Sec. 11) Established the position for the corner at the intersection of the South line of Government Lot 3 (being parallel to the south line of the Section) with the line between Government Lots 4 & 5 (being parallel to the west line of the Section).
(SMC) Established the position for the SMC at the water's edge of Bass Lake, and midway between the E-W 1/4 line and the South line of Section 11 (the south line of the Section for this purpose being a straight line between the WCMC's on the east and west shores of Bass Lake as recorded in Liber C14, pages 222, 223). The WCSMC monumented is about 8' west of the marshy margin of the lake and about 90' west of the water's edge.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 3" W.Birch N54°E 15.1' mrkd "GL3 BT" 6" Maple in clump S61°E 19.6' "GL5 BT" 6" W.Birch S02°E 34.3' do 4" W.Pine S30°W 27.1' "GL4 BT" Set sq'd cedar post adjacent. E= 7862435.061 N= 142072.463
(SMC) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 7" Maple N81°W 5.15' mrkd "WC BT" 3" Balsam N25°W 9.2' do 4" Balsam N69°E 5.85' do 4" Balsam S47°W 2.4' do Set sq'd cedar post adjacent. E= 7862694.575 N= 142064.548

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID RL0456: N= 142561.037 m. E= 7864413.728 m.

Signed by [Signature]
Surveyor's Michigan License No. 33986

Date 07/13/2015

For the Michigan Department of Natural Resources, Forest Resources Division

