LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name:	ne: <u>Stephan J. Szyszkoski</u>		Field Survey Date:		See below			
For corner(s) in:	Iron	Count	y ₁ AB	CDE	FG	HIJ	K L M,	
Original Public Lar S S	T R R	Corner Code	2 - 6 - 3 - 4 - 7	5	4	3- 2	1 2 3	
s s	TR		5 6 18	1.7			5	
Property Corner		1/16 Corner Code	0		16	15 14	13-6	
a. S14	T 44N R 32W	11 (GCDB 520420)	— 8 <u>19</u>	20	21	22 23	7	
b. S <u>15</u>	T 44N R 32W	16 (GCDB 460400)	9				9	
b. S <u>22</u>	T 44N R 32W	2 (GCDB 460400)	 10 30	29	-28	27 26		
			11			+ + +	11	
			12 - 31	32 -	33	34 35	36 12	
Part A. Corner History			13 A B	CDE	FG	HIJ	K L M	

- a. Southwest 1/16 corner, Section 14 T44N-R32W. Not previously monumented.
- b. East 1/16 corner between Sections 15 and 22 T44N-R32W. 1984 Established by K.L.Sackett RLS midway and on line between 1/4 corner west and Section corner east. Set 1"IDx32" I.pipe with 4" alum. MDNR cap. 6" Hemlock N48°E 20.9'; 12" Maple S30°W 33.9'; 5" Maple squared S12°W 1.8'.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

- a. May 14 2018. Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corner, those to the south and west being monumented.
- b. May 14 2018. Found the 1984 monument in good condition, substantially at the record position, and at record bearing and distance from the squared Maple S12°W, in good condition with 4 overgrown blazes. The Hemlock and Maple S30W BTs are dead and down. Accepted the monument as a careful and faithful establishment of the position of the corner.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

b. Found 1"ID I.pipe with 4" alum. MDNR cap. a. Set 5/8"x24" rebar with plastic MDNR cap. Set measuring nail with MDNR tag in the side of: Set measuring nail with MDNR tag in the side of: 12" Sugar S17°W 1.65' old blazes (1984 wit.) 7" Cedar N69°E 25.5' mrkd "1/16S BT" 5" Sugar N60°E 7.4' mrkd "1/16S BT" 5" B.Ash S47°E 3.4' do 6" Sugar S74°E 11.35' do 6" Cedar S27°W 12.0' do 9" Sugar N61°W 13.9' do 9" Cedar S73°W 0.8' do Set sq'd cedar post adjacent. E= 7901315.30 N= 159020.36 E= 7900501.94 N= 158629.71

05/30/2018

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00

Stephen | Lypoylost.

Professional Surveyor's License No.: 33986 page 1 of 1 Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

STEPHAN J. SZYSZKOSKI ROFESSIONAL SURVEYOR No. 33986 OFESSION

OF MIC